

DOCKET NO: 199894US8

OBLON
SPIVAK
MCCLELLAND
MAIER
&
NEUSTADT
P.C.

ATTORNEYS AT LAW

BRADLEY D. LYTLE

(703) 412-6489

BLYTLE@OBLON.COM EDWIN D. GARLEPP

(703) 413-3000 EGARLEPP@OBLON.COM

COMMISSIONER FOR PATENTS WASHINGTON, D.C. 20231

RE: U.S. Application

Serial No: 09/832,885 Filed: April 12, 2001

Inventor: Naoki Tsukiji et al.

For: Semiconductor Laser Device for Use in . . .

SIR:

Attached hereto for filing are the following papers:

PRELIMINARY AMENDMENT (w/ Marked-up Copy)

Our check in the amount of \$_-0-- is attached covering any required fees. In the event that any variance exists between the amount enclosed and the Patent Office charges for filing the above-noted documents, including any fees required under 37 CFR 1.136 for any necessary Extension of Time to make the filing of the attached documents timely, please charge or credit our Deposit Account No. 15-0030. Further, if these papers are not considered timely filed, then a petition is hereby made under 37 C.F.R. 1.136 for the necessary extension of time. A duplicate copy of this sheet is attached.

22850

Tel. No.: (703) 413-3000 Fax No.: (703) 413-2220

BDL:EDG:eac

Respectfully submitted,

OBLON, SPIVAK, McCLELLAND,

MAKER & NEUSTADT, P

Bradley D. Lytle Attorney of Record

Autorney of Record Registration No. 40,073

Edwin D. Garlepp

Registration No. 45,330

RECEIVED SEP-4 2002 TC:2800 MAIL ROOM Docket No.: 199894US8

#10/Pr-andth

IN THE UNITED STATES PATENT & TRADEMARK OFFICE

IN RE APPLICATION OF

NAOKI TSUKIJI ET AL.

GROUP: 2881

SERIAL NO: 09/832,885

EXAMINER:

FILED: APRIL 12, 2001

FOR: SEMICONDUCTOR LASER DEVICE FOR USE IN A LASER MODULE

PRELIMINARY AMENDMENT UNDER 37 C.F.R. §1.115

ASSISTANT COMMISSIONER FOR PATENTS WASHINGTON, D.C. 20231

SIR:

Prior to examination on the merits, please amend the above-identified patent application as follows:

IN THE SPECIFICATION

Pages 3-4, paragraph 0009, please delete the paragraph and insert the following new paragraph:

The WDM coupler 62 multiplexes the laser beams outputted from the polarization-multiplexing couplers 61a and 61b, and outputs the multiplexed light beams as a pumping light beam to external isolator 60, which outputs the beam to amplifying fiber 64 via WDM coupler 65. Signal light beams to be amplified are input to amplifying fiber 64 from signal light inputting fiber 69 via polarization-dependent isolator 63. The amplified signal light beams are Raman-amplified by being multiplexed with the pumping light beams and input to

1